



EUROPEAN  
COMMISSION

Brussels, 18.5.2015  
COM(2015) 201 final

ANNEX 1

**ANNEX**

**to the**

**Proposal for a Council Regulation**

**amending Regulation (EU) No 1387/2013 suspending the autonomous Common Customs  
Tariff duties on certain agricultural and industrial products**

## ANNEX

Regulation (EU) No 1387/2013 is amended as follows:

(1) Annex I is amended as follows:

(a) between the title and the table, the note is replaced by the following note:

‘(\*) Suspension relating to a product in this Annex with regard to which the CN or TARIC code or the product description or the mandatory review date were amended by Council Regulation (EU) No 722/2014 of 24 June 2014 amending Regulation (EU) No 1387/2013 suspending the autonomous Common Customs Tariff duties on certain agricultural and industrial products (OJ L 192, 1.7.2014, p. 9)’, by Council Regulation (EU) No 1341/2014 of 15 December 2014 amending Regulation (EU) No 1387/2013 suspending the autonomous Common Customs Tariff duties on certain agricultural and industrial products and by Council Regulation (EU) .../... of ... amending Regulation (EU) No 1387/2013 suspending the autonomous Common Customs Tariff duties on certain agricultural and industrial products (OJ ...)’;

(b) the following rows for the products are inserted following the order of the CN codes indicated in the first column of the table;

| CN code                                          | TARIC          | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Rate of autonomous duty | Date foreseen for mandatory review |
|--------------------------------------------------|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------------------|
| *ex 2009 89 73<br>ex 2009 89 73                  | 11<br>13       | Passion fruit juice and passion fruit juice concentrate, whether or not frozen:<br>— with a Brix value of 13,7 or more but not more than 55,<br>— of a value of more than € 30 per 100 kg net weight,<br>— in immediate packings of a content of 50 litres or more, and<br>— with added sugar<br>for the use in the manufacture of products of food or drink industry<br>(1)                                                                                                                                                                                                                                                                                                                                                          | 0 %                     | 31.12.2019                         |
| *ex 2009 89 99                                   | 94             | Coconut water<br>— unfermented,<br>— not containing added spirit or sugar, and<br>— in immediate packing of a content of 50 litres or more<br>(2)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 0 %                     | 31.12.2016                         |
| *ex 2207 20 00<br>ex 2207 20 00<br>ex 3820 00 00 | 20<br>80<br>20 | Feedstock consisting of by weight:<br>— 88 % or more but not more than 92 % of ethanol,<br>— 2,2 % or more but not more than 2,7 % of monoethylene glycol,<br>— 1,0 % or more but not more than 1,3 % of methylethylketone,<br>— 0,36 % or more but not more than 0,40 % of anionic surfactant (ca.30 % active),<br>— 0,0293 % or more but not more than 0,0396 % of methyl isopropylketone,<br>— 0,0195 % or more but not more than 0,0264 % of 5 methyl-3-heptanone,<br>— 10 ppm or more but not more than 12 ppm of denatonium benzoate (Bitrex);<br>— not more than 0,01 of perfumes<br>— 6,5 % or more but not more than 8,0 % of water.<br>for use in the manufacture of screenwash concentrate and other de-icing preparations | 0 %                     | 31.12.2018                         |

| CN code        | TARI<br>C | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Rate of<br>autonomous<br>duty | Date<br>foreseen for<br>mandatory<br>review |
|----------------|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------|
|                |           | (1)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                               |                                             |
| ex 2710 19 99  | 20        | Catalytic de-waxed base oil, synthesised from gaseous hydrocarbons, followed by a heavy paraffin conversion process (HPC), containing:<br>— not more than 1 mg/kg of sulphur<br>— more than 99 % by weight of saturated hydrocarbons<br>— more than 75 % by weight of n- and iso-paraffinic hydrocarbons with a carbon chain length of 18 or more but not more than 50; and<br>— a kinematic viscosity at 40 °C of more than 6,5 mm <sup>2</sup> /s, or<br>— a kinematic viscosity at 40 °C of more than 11 mm <sup>2</sup> /s with a viscosity index of 120 or more                                                   | 0 %                           | 31.12.2019                                  |
| *ex 2818 10 91 | 20        | Sintered corundum with a micro crystalline structure, consisting of aluminium oxide (CAS RN 1344-28-1), magnesium aluminate (CAS RN 12068-51-8) and the rare earth aluminates of yttrium, lanthanum, and neodymium, with a content by weight (calculated as oxides) of:<br>— 94 % or more, but less than 98,5 % of aluminium oxide,<br>— 2 % (± 1,5 %) of magnesium oxide,<br>— 1 % (± 0,6 %) of yttrium oxide,<br>And<br>— either 2 % (± 1,2 %) of lanthanum oxide or<br>— 2 % (± 1,2 %) of lanthanum oxide and neodymium oxide,<br>with less than 50 % of the total weight having a particle size of more than 10 mm | 0 %                           | 31.12.2015                                  |
| ex 2827 60 00  | 10        | Sodium iodide (CAS RN 7681-82-5)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 0 %                           | 31.12.2019                                  |
| ex 2841 70 00  | 30        | Hexaammonium heptamolybdate, anhydrous (CAS RN 12027-67-7) or as tetrahydrate (CAS RN 12054-85-2)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 0 %                           | 31.12.2019                                  |
| ex 2903 39 90  | 35        | Pentafluoroethane (CAS RN 354-33-6)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 0 %                           | 31.12.2019                                  |
| ex 2903 79 19  | 10        | Trans-1-chloro-3,3,3-trifluoropropene (CAS RN 102687-65-0)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 0 %                           | 31.12.2019                                  |
| ex 2904 90 95  | 80        | 1-Chloro-2-nitrobenzene (CAS RN 88-73-3)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 0 %                           | 31.12.2019                                  |
| ex 2905 22 00  | 10        | Linalool (CAS RN 78-70-6) containing by weight 90,7 % or more of (3R)-(-)-Linalool (CAS RN 126-91-0)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 0 %                           | 31.12.2019                                  |
| ex 2907 12 00  | 30        | p-Cresol (CAS RN 106-44-5)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 0 %                           | 31.12.2019                                  |
| ex 2907 29 00  | 25        | 4-Hydroxybenzyl alcohol (CAS RN 623-05-2)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 0 %                           | 31.12.2019                                  |
| ex 2907 29 00  | 65        | 2,2'-Methylenebis(6-cyclohexyl-p-cresol) (CAS RN 4066-02-8)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 0 %                           | 31.12.2019                                  |
| ex 2909 60 00  | 30        | 3,6,9-Triethyl-3,6,9-trimethyl-1,4,7-triperoxonane (CAS RN 24748-23-0), dissolved in isoparaffinic hydrocarbons                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 0 %                           | 31.12.2019                                  |
| ex 2914 69 90  | 50        | Reaction mass of 2-(1,2-dimethylpropyl)anthraquinone (CAS RN 68892-28-4) and 2-(1,1-dimethylpropyl)anthraquinone (CAS RN 32588-54-8)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 0 %                           | 31.12.2019                                  |
| ex 2916 39 90  | 18        | 2,4-Dichlorophenylacetic acid (CAS RN 19719-28-9)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 0 %                           | 31.12.2019                                  |
| ex 2916 39 90  | 23        | (2,4,6-Trimethylphenyl)acetyl chloride (CAS RN 52629-46-6)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 0 %                           | 31.12.2019                                  |
| ex 2917 39 95  | 50        | 1,4,5,8-Naphthalenetetracarboxylic acid-1,8-monoanhydride (CAS RN 52671-72-4)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 0 %                           | 31.12.2019                                  |
| ex 2917 39 95  | 60        | Perylene-3,4:9,10-tetracarboxylic dianhydride(CAS RN 128-69-8)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 0 %                           | 31.12.2019                                  |

| CN code        | TARI C | Description                                                                                                                                                                                                                                                  | Rate of autonomous duty | Date foreseen for mandatory review |
|----------------|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------------------|
| ex 2918 29 00  | 70     | 3,5-Diiodosalicylic acid (CAS RN 133-91-5)                                                                                                                                                                                                                   | 0 %                     | 31.12.2019                         |
| ex 2918 30 00  | 70     | 2-[4-Chloro-3-(chlorosulphonyl)benzoyl]benzoic acid (CAS RN 68592-12-1)                                                                                                                                                                                      | 0 %                     | 31.12.2019                         |
| ex 2918 99 90  | 55     | Stearyl glycyrrhetinate(CAS RN 13832-70-7)                                                                                                                                                                                                                   | 0 %                     | 31.12.2019                         |
| ex 2918 99 90  | 65     | Acetic acid, difluoro[1,1,2,2-tetrafluoro-2-(pentafluoroethoxy)ethoxy]-, ammonium salt (CAS RN 908020-52-0)                                                                                                                                                  | 0 %                     | 31.12.2019                         |
| ex 2918 99 90  | 75     | 3,4-Dimethoxybenzoic acid (CAS RN 93-07-2)                                                                                                                                                                                                                   | 0 %                     | 31.12.2019                         |
| ex 2921 42 00  | 40     | Sodium sulphaniate (CAS RN 515-74-2), also in form of its mono- or dihydrates (CAS RN 12333-70-0 or 6106-22-5)                                                                                                                                               | 0 %                     | 31.12.2019                         |
| ex 2922 49 85  | 55     | (E)-Ethyl 4-(dimethylamino)but-2-enoate maleate (CUS 0138070-7)                                                                                                                                                                                              | 0 %                     | 31.12.2019                         |
| ex 2923 90 00  | 20     | Tetramethylammonium hydrogen phthalate (CAS RN 79723-02-7)                                                                                                                                                                                                   | 0 %                     | 31.12.2019                         |
| ex 2924 19 00  | 35     | Acetamide (CAS RN 60-35-5)                                                                                                                                                                                                                                   | 0 %                     | 31.12.2019                         |
| ex 2924 29 98  | 23     | Benalaxyl-M (ISO) (CAS RN 98243-83-5)                                                                                                                                                                                                                        | 0 %                     | 31.12.2019                         |
| ex 2924 29 98  | 33     | N-(4-Amino-2-ethoxyphenyl)acetamide (CAS RN 848655-78-7)                                                                                                                                                                                                     | 0 %                     | 31.12.2019                         |
| ex 2924 29 98  | 73     | Napropamide (ISO) (CAS RN 15299-99-7)                                                                                                                                                                                                                        | 0 %                     | 31.12.2019                         |
| *ex 2927 00 00 | 35     | C.C'-Azodi(formamide) (CAS RN 123-77-3) in the form of yellow powder with a decomposition temperature of 180°C or more but not more than 220°C used as a foaming agent in the manufacture of thermoplastic resins, elastomer and cross-linked polythene foam | 0 %                     | 31.12.2019                         |
| ex 2928 00 90  | 13     | Cymoxanil (ISO) (CAS RN 57966-95-7)                                                                                                                                                                                                                          | 0 %                     | 31.12.2019                         |
| ex 2928 00 90  | 18     | Acetone oxime (CAS RN 127-06-0) of a purity by weight of 99 % or more                                                                                                                                                                                        | 0 %                     | 31.12.2019                         |
| ex 2930 90 99  | 16     | 3-(Dimethoxymethylsilyl)-1-propanethiol (CAS RN 31001-77-1)                                                                                                                                                                                                  | 0 %                     | 31.12.2019                         |
| *ex 2930 90 99 | 21     | [2,2'-Thio-bis(4- <i>tert</i> -octylphenolato)]-n-butylamine nickel (CAS RN 14516-71-3)                                                                                                                                                                      | 0 %                     | 31.12.2016                         |
| ex 2930 90 99  | 27     | 2-[(4-Amino-3-methoxyphenyl)sulphonyl]ethyl hydrogen sulphate (CAS RN 26672-22-0)                                                                                                                                                                            | 0 %                     | 31.12.2019                         |
| ex 2930 90 99  | 33     | 2-Amino-5- {[2-(sulfoxy)ethyl]sulfonyl}benzenesulfonic acid (CAS RN 42986-22-1)                                                                                                                                                                              | 0 %                     | 31.12.2019                         |
| ex 2933 39 99  | 11     | 2-(Chloromethyl)-4-(3-methoxypropoxy)-3-methylpyridine hydrochloride(CAS RN 153259-31-5)                                                                                                                                                                     | 0 %                     | 31.12.2019                         |
| ex 2933 39 99  | 21     | Boscalid (ISO) (CAS RN 188425-85-6)                                                                                                                                                                                                                          | 0 %                     | 31.12.2019                         |
| ex 2933 39 99  | 31     | 2-(Chloromethyl)-3-methyl-4-(2,2,2-trifluoroethoxy)pyridine hydrochloride(CAS RN 127337-60-4)                                                                                                                                                                | 0 %                     | 31.12.2019                         |
| ex 2933 59 95  | 10     | 6-Amino-1,3-dimethyluracil (CAS RN 6642-31-5)                                                                                                                                                                                                                | 0 %                     | 31.12.2019                         |
| ex 2933 69 80  | 75     | Metamitron (ISO) (CAS RN 41394-05-2)                                                                                                                                                                                                                         | 0 %                     | 31.12.2019                         |
| ex 2933 99 80  | 11     | Fenbuconazole (ISO) (CAS RN 114369-43-6)                                                                                                                                                                                                                     | 0 %                     | 31.12.2019                         |

| CN code                        | TARI<br>C | Description                                                                                                                                                                                                                                                                                                                                                                                       | Rate of<br>autonomous<br>duty | Date<br>foreseen for<br>mandatory<br>review |
|--------------------------------|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------|
| ex 2933 99 80                  | 12        | Myclobutanil (ISO) (CAS RN 88671-89-0)                                                                                                                                                                                                                                                                                                                                                            | 0 %                           | 31.12.2019                                  |
| ex 2933 99 80                  | 19        | 2-(2,4-Dichlorophenyl)-3-(1H-1,2,4-triazol-1-yl)propan-1-ol (CAS RN 112281-82-0)                                                                                                                                                                                                                                                                                                                  | 0 %                           | 31.12.2019                                  |
| ex 2934 99 90                  | 10        | Fluralaner (INN) (CAS RN 864731-61-3)                                                                                                                                                                                                                                                                                                                                                             | 0 %                           | 31.12.2019                                  |
| ex 2934 99 90                  | 16        | Difenoconazole (ISO) (CAS RN 119446-68-3)                                                                                                                                                                                                                                                                                                                                                         | 0 %                           | 31.12.2019                                  |
| ex 2934 99 90                  | 19        | 2-[4-(Dibenzo[b,f][1,4]thiazepin-11-yl)piperazin-1-yl] ethanol(CAS RN 329216-67-3)                                                                                                                                                                                                                                                                                                                | 0 %                           | 31.12.2019                                  |
| ex 2935 00 90                  | 10        | Florasulam (ISO) (CAS RN 145701-23-1)                                                                                                                                                                                                                                                                                                                                                             | 0 %                           | 31.12.2019                                  |
| ex 3204 12 00                  | 60        | Colourant C.I. Acid Red 52 (CAS RN 3520-42-1 ) and preparations based thereon with a colourant C.I. Acid Red 52 content of 97 % or more by weight                                                                                                                                                                                                                                                 | 0 %                           | 31.12.2019                                  |
| ex 3204 13 00                  | 50        | Colourant C.I Basic Violet 11 (CAS RN 2390-63-8) and preparations based thereon with a colourant C.I Basic Violet 11 content of 90 % or more by weight                                                                                                                                                                                                                                            | 0 %                           | 31.12.2019                                  |
| ex 3204 13 00                  | 60        | Colourant C.I Basic Red 1:1 (CAS RN 3068-39-1) and preparations based thereon with a colourant C.I Basic Red 1:1 content of 90 % or more by weight                                                                                                                                                                                                                                                | 0 %                           | 31.12.2019                                  |
| ex 3204 14 00                  | 10        | Colourant C.I. Direct Black 80 (CAS RN 8003-69-8) and preparations based thereon with a colourant C.I. Direct Black 80 content of 90 % or more by weight                                                                                                                                                                                                                                          | 0 %                           | 31.12.2019                                  |
| ex 3204 14 00                  | 20        | Colourant C.I. Direct Blue 80 (CAS RN 12222-00-3) and preparations based thereon with a colourant C.I. Direct Blue 80 content of 90 % or more by weight                                                                                                                                                                                                                                           | 0 %                           | 31.12.2019                                  |
| ex 3204 14 00                  | 30        | C.I. Colourant Direct Red 23 (CAS RN 3441-14-3 ) and preparations based thereon with a colourant C.I. Direct Red 23 content of 90 % or more by weight                                                                                                                                                                                                                                             | 0 %                           | 31.12.2019                                  |
| ex 3204 17 00                  | 45        | Colourant C.I. Pigment Yellow 174 (CAS RN 4118-16-5), highly resinated pigment (approx. 35 % disproportionate resin), with a purity of 98 % by weight or more, in the form of extruded beads with a moisture content of not more than 1 % by weight                                                                                                                                               | 0 %                           | 31.12.2018                                  |
| ex 3204 17 00                  | 67        | Colourant C.I. Pigment Red 57:1 (CAS RN 5281-04-9) with a purity of 98 % by weight or more, in the form of extruded beads, with a moisture content of not more than 1 % by weight.                                                                                                                                                                                                                | 0 %                           | 31.12.2018                                  |
| ex 3204 90 00                  | 10        | Colourant C.I Solvent Yellow 172 (also known as C.I. Solvent Yellow 135) (CAS RN 68427-35-0) and preparations based thereon with a colourant C.I Solvent Yellow 172 (also known as C.I. Solvent Yellow 135) content of 90 % or more by weight                                                                                                                                                     | 0 %                           | 31.12.2019                                  |
| ex 3212 10 00<br>ex 7607 20 90 | 10<br>30  | Metallised film:<br>— consisting of eight or more layers of aluminium (CAS RN 7429-90-5) of a purity of 99,8 % or more,<br>— with an optical density of each aluminium layer of not more than 3.0,<br>— with each aluminium layer separated by a resin layer,<br>— on a carrier film of PET, and<br>— on rolls of up to 50 000 metres in length                                                   | 0 %                           | 31.12.2019                                  |
| ex 3808 94 20                  | 30        | Bromochloro-5,5-dimethylimidazolidine-2,4-dione (CAS RN 32718-18-6) containing:<br>— 1,3-Dichloro-5,5-dimethylimidazolidine-2,4-dione (CAS RN 118-52-5),<br>— 1,3-Dibromo-5,5-dimethylimidazolidine-2,4-dione (CAS RN 77-48-5),<br>— 1-Bromo,3-chloro-5,5-dimethylimidazolidine-2,4-dione (CAS RN 16079-88-2),<br>and<br>— 1-Chloro,3-bromo-5,5-dimethylimidazolidine-2,4-dione (CAS RN 126-06-7) | 0 %                           | 31.12.2019                                  |

| CN code                         | TARI<br>C | Description                                                                                                                                                                                                                                                                                                                                                                                                                                   | Rate of<br>autonomous<br>duty | Date<br>foreseen for<br>mandatory<br>review |
|---------------------------------|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------|
| ex 3811 21 00                   | 23        | Additives containing:<br>— polyisobutene succinimide derived from reaction of polyethylenepropylamide with polyisobutenyl succinic anhydride (CAS RN 84605-20-9),<br>— containing more than 31,9 % but not more than 43,3 % by weight of mineral oils,<br>— not more than 0,05 % by weight chlorine, and<br>— having a total base number (TBN) greater than 20,<br>for use in the manufacture of additives blends for lubricating oils<br>(1) | 0 %                           | 31.12.2019                                  |
| *ex 3811 21 00                  | 53        | Additives containing:<br>— overbased calcium petroleum sulphonates (CAS 68783-96-0) with a sulphonate content by weight of 15 % or more, but not more than 30 % and<br>— by weight more than 40 % but not more than 60 % of mineral oil,<br>having a total base number of 280 or more but not more than 420,<br>for use in the manufacture of lubricating oils<br>(1)                                                                         | 0 %                           | 31.12.2019                                  |
| *ex 3811 21 00                  | 73        | Additives containing:<br>— borated succinimide compounds (CAS RN 134758-95-5),<br>— mineral oils, and<br>— having a total base number (TBN) greater than 40,<br>for use in the manufacture of additive mixtures for lubricating oils<br>(1)                                                                                                                                                                                                   | 0 %                           | 31.12.2018                                  |
| ex 3812 30 29                   | 10        | 4,4'-Isopropylidenediphenol C12-15 alcohol phosphite containing by weight 1 % or more but not more than 3 % of bisphenol A (CAS RN 96152-48-6)                                                                                                                                                                                                                                                                                                | 0 %                           | 31.12.2019                                  |
| ex 3824 90 92                   | 82        | T-butylchloride dimethylsilane (CAS RN 18162-48-6) solution in toluene                                                                                                                                                                                                                                                                                                                                                                        | 0 %                           | 31.12.2019                                  |
| *ex 3824 90 92                  | 83        | Preparation, consisting of two or more of the following glycols:<br>— dipropylene glycol<br>— tripropylene glycol<br>— tetrapropylene glycol or<br>— pentapropylene glycol                                                                                                                                                                                                                                                                    | 0 %                           | 31.12.2017                                  |
| *ex 3824 90 93                  | 46        | Sodium hydrogen 3-aminonaphthalene-1,5-disulfonate (CAS RN 4681-22-5) containing by weight:<br>— not more than 20 % of disodium sulphate,<br>— not more than 5 % of sodium chloride                                                                                                                                                                                                                                                           | 0 %                           | 31.12.2015                                  |
| *ex 3901 10 10<br>ex 3901 90 90 | 20<br>50  | High flow linear low density polyethylene-1-butene (LLDPE) (CAS RN 25087-34-7) in form of powder, with<br>— a melt flow rate (MFR 190 °C/2,16 kg) of 16 g/10 min or more, but not more than 24 g/10 min and<br>— a density (ASTM D 1505) of 0,922 g/cm <sup>3</sup> or more, but not more than 0,926 g/cm <sup>3</sup> and<br>— a vicat softening temperature of min. 94 °C                                                                   | 0 %                           | 31.12.2019                                  |
| *ex 3901 10 10                  | 30        | Linear low-density polyethylene (LLDPE) (CAS RN 9002-88-4) in the form of powder, with<br>— not more than 5 % by weight of comonomer,<br>— a melt flow rate of 15 g/10 min or more, but not more than 60 g/10 min and<br>— a density of 0,922 g/cm <sup>3</sup> or more, but not more than 0,928 g/cm <sup>3</sup>                                                                                                                            | 0 %                           | 31.12.2018                                  |
| *ex 3901 90 90                  | 60        | Linear low-density polyethylene ( LLDPE) (CAS RN 9002-88-4) in the form of powder, with<br>— more than 5 %, but not more than 8 % by weight of comonomer,<br>— a melt flow rate of 15 g/10 min or more, but not more than 60 g/10 min and                                                                                                                                                                                                     | 0 %                           | 31.12.2018                                  |

| CN code        | TARI<br>C | Description                                                                                                                                                                                                                                                                                                                         | Rate of<br>autonomous<br>duty | Date<br>foreseen for<br>mandatory<br>review |
|----------------|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------|
|                |           | — a density of 0,922 g/cm <sup>3</sup> or more, but not more than 0,928 g/cm <sup>3</sup>                                                                                                                                                                                                                                           |                               |                                             |
| *ex 3903 19 00 | 40        | Crystalline polystyrene with:<br>— a melting point of 268 °C or more but not more than 272 °C<br>— a setting point of 232 °C or more but not more than 247 °C,<br>— whether or not containing additives and filling material                                                                                                        | 0 %                           | 31.12.2016                                  |
| ex 3903 90 90  | 45        | Preparation, in form of powder, containing by weight:<br><br>— 86 % or more but not more than 90 % of styrene-acrylic-copolymer and<br>— 9 % or more but not more than 11 % of fatty acid ethoxylate (CAS RN 9004-81-3)                                                                                                             | 0 %                           | 31.12.2019                                  |
| ex 3903 90 90  | 55        | Preparation, in form of an aqueous suspension, containing by weight:<br>— 25 % or more but not more than 26 % of styrene-acrylic-copolymer and<br>— 5 % or more but not more than 6 % of glycol                                                                                                                                     | 0 %                           | 31.12.2019                                  |
| ex 3908 90 00  | 70        | Copolymer containing:<br>— 1,3-benzenedimethanamine (CAS RN 1477-55-0) and<br>— adipic acid (CAS RN 124-04-9)<br>whether or not containing isophthalic acid (CAS RN 121-91-5)                                                                                                                                                       | 0 %                           | 31.12.2019                                  |
| ex 3911 90 19  | 60        | Formaldehyde, polymer with 1,3-dimethylbenzene and tert-butyl-phenol (CAS RN 60806-48-6)                                                                                                                                                                                                                                            | 0 %                           | 31.12.2019                                  |
| ex 3911 90 19  | 70        | Preparation, containing:<br>— Cyanic acid, C,C'-((1-methylethylidene)di-4,1-phenylene) ester, homopolymer (CAS RN 25722-66-1),<br>— 1,3-Bis(4-cyanophenyl)propane (CAS RN 1156-51-0),<br>— in a solution of butanone (CAS RN 78-93-3) with a content of less than 50 % by weight                                                    | 0 %                           | 31.12.2019                                  |
| *ex 3912 20 19 | 10        | Nitrocellulose (CAS RN 9004-70-0)                                                                                                                                                                                                                                                                                                   | 0 %                           | 31.12.2016                                  |
| *ex 3919 10 80 | 57        | Reflecting sheet:                                                                                                                                                                                                                                                                                                                   | 0 %                           | 31.12.2018                                  |
| ex 3919 90 00  | 30        | — of a polycarbonate or acrylic polymer film embossed on one side in a regular shaped pattern                                                                                                                                                                                                                                       |                               |                                             |
| ex 3920 61 00  | 30        | — covered on one or both sides with one or more layers of plastic or metallisation, and<br>— whether or not covered on one side with a self-adhesive layer and a release sheet                                                                                                                                                      |                               |                                             |
| *ex 3919 10 80 | 67        | Self-adhesive reflecting sheet whether or not in segmented pieces:                                                                                                                                                                                                                                                                  | 0 %                           | 31.12.2018                                  |
| ex 3919 90 00  | 46        | — showing a regular pattern,<br>— with or without an application tape layer,<br>— consisting of a film of acrylic polymer followed by a layer of poly(methyl methacrylate) or polycarbonate containing microprisms,<br>— whether or not containing an additional layer of polyester and<br>— an adhesive with a final release sheet |                               |                                             |
| *ex 3919 90 00 | 48        | Transparent poly(vinyl chloride) film:<br>— coated on one side with an acrylic UV-sensitive adhesive with an adhesive strength of 70 N/m or more, which is reduced upon irradiation,<br>— with a polyester liner<br>— with a total thickness without release liner of 78 µm or more                                                 | 0 %                           | 31.12.2019                                  |

| CN code        | TARI<br>C | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Rate of<br>autonomous<br>duty | Date<br>foreseen for<br>mandatory<br>review |
|----------------|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------|
| ex 3920 10 28  | 30        | Printed embossed film<br>— of polymers of ethylene<br>— having a gravity of 0,94g/cm <sup>3</sup> or more<br>— of a thickness of 0,019mm ± 0,003mm<br>— with permanent graphics consisting of two different alternating designs whose individual length is 525 mm or more                                                                                                                                                                                                                                                              | 0 %                           | 31.12.2019                                  |
| *ex 3920 62 19 | 60        | Poly (ethylene terephthalate) film:<br>— of a thickness of not more than 20µm,<br>— coated on at least one side with a gas barrier layer consisting of a polymeric matrix in which silica or aluminium oxide has been dispersed and of a thickness of not more than 2µm                                                                                                                                                                                                                                                                | 0 %                           | 31.12.2017                                  |
| ex 3920 69 00  | 50        | Monolayer, biaxially oriented film:<br>— composed of more than 85 % by weight of poly(lactic acid) and not more than 10,50 % by weight of modified poly(lactic acid) based polymer, poly-glycol ester and talc,<br>— having a thickness of 20 µm or more but not more than 120 µm<br>— biodegradable and compostable (as determined by the method EN 13432)                                                                                                                                                                            | 0 %                           | 31.12.2019                                  |
| ex 3920 69 00  | 60        | Monolayer, transverse oriented, shrink film:<br>— composed of more than 80 % by weight of poly(lactic acid) and not more than 15,75 % by weight of additives of modified poly(lactic acid),<br>— having a thickness of 45 µm or more but not more than 50 µm,<br>— biodegradable and compostable (as determined by the method EN 13432)                                                                                                                                                                                                | 0 %                           | 31.12.2019                                  |
| ex 3920 79 10  | 10        | Sheets of painted vulcanised fibre-board with a thickness of not more than 1,5 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 0 %                           | 31.12.2019                                  |
| ex 3920 99 28  | 65        | Matt, thermoplastic polyurethane foil in rolls with:<br>— a width of 1640 mm (± 10 mm),<br>— a gloss of 3,3 degrees or more but not more than 3,8 (as determined by the method ASTM D2457),<br>— a surface roughness of 1,9 Ra or more but not more than 2,8 Ra (as determined by the method ISO 4287),<br>— a thickness of more than 365 µm but not more than 760 µm,<br>— a hardness of 90 (± 4) (as determined by the method: Shore A (ASTM D2240)),<br>— an elongation to break of 470 % (as determined by the method: EN ISO 527) | 0 %                           | 31.12.2019                                  |
| ex 3920 99 28  | 75        | Thermoplastic polyurethane foil in rolls with:<br>— a width of more than 900 mm but not more than 1016 mm,<br>— a matt finish,<br>— a thickness of 0,43 mm (± 0.03 mm),<br>— an elongation to break of 420 % or more but not more than 520 %,<br>— a tensile strength of 55 N/mm <sup>2</sup> (± 3) (as determined by the method EN ISO 527)<br>— a hardness of 90 (± 4) (as determined by the method: Shore A [ASTM D2240]),<br>— wrinkle inside (waves) of 6,35 mm,<br>— a flatness of 0,025 mm                                      | 0 %                           | 31.12.2019                                  |
| ex 3921 90 60  | 30        | Heat-, infra- and UV insulating poly(vinyl butyral) film:<br>— laminated with a metal layer with a thickness of 0,05 mm(±0,01 mm),<br>— containing by weight 29,75 % or more but not more than 40,25 % of triethyleneglycol di (2-ethyl hexanoate) as plasticizer,<br>— with a light transmission of 70 % or more (as determined by the ISO 9050 standard);<br>— with an UV transmission of 1 % or less (as determined by the ISO 9050 standard);<br>— with a total thickness of 0,43 mm (± 0,043 mm)                                  | 0 %                           | 31.12.2019                                  |
| ex 6804 21 00  | 10        | Discs<br>— of synthetic diamonds which are agglomerated with a metal alloy, ceramic alloy or plastic alloy,                                                                                                                                                                                                                                                                                                                                                                                                                            | 0 %                           | 31.12.2019                                  |



| CN code                                         | TARI<br>C      | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Rate of<br>autonomous<br>duty | Date<br>foreseen for<br>mandatory<br>review |
|-------------------------------------------------|----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------|
|                                                 |                | — having a self-sharpening effect by constant release of the diamonds,<br>— suitable for abrasive cutting of wafers,<br>— whether or not containing a hole in the centre,<br>— whether or not on a support                                                                                                                                                                                                                                                                                                                                                                                       |                               |                                             |
| ex 7409 11 00<br>ex 7409 19 00<br>ex 7410 11 00 | 10<br>10<br>20 | Refined copper foil and -strips of a thickness of not more than 400 µm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | 0 %                           | 31.12.2019                                  |
| *ex 7606 12 92<br>ex 7607 11 90                 | 30<br>50       | Aluminium and magnesium alloy strip <i>or foil</i> :<br>— in rolls,<br>— of a thickness of 0,14 mm or more but not more than 0,40 mm,<br>— a width of 12,5 mm or more but not more than 359 mm,<br>— a tensile strength of 285 N/mm <sup>2</sup> or more, and<br>— an elongation at break of 1 % or more, and<br>containing by weight:<br>— 93,3 % or more of aluminium,<br>— 0,8 % or more but not more than 5 % of magnesium, and<br>— not more than 1,8 % of other elements                                                                                                                   | 0 %                           | 31.12.2017                                  |
| *ex 7607 11 90                                  | 60             | Plain aluminium foil with the following parameters:<br>— an aluminium content of 99,98 % or more<br>— a thickness of 0,070 mm or more but not more than 0,125 mm<br>— with a cubic texture<br>of a kind used for high voltage etching                                                                                                                                                                                                                                                                                                                                                            | 0 %                           | 31.12.2016                                  |
| ex 7616 99 10                                   | 30             | Aluminium engine bracket, with dimensions of:<br>— height of more than 10 mm but not more than 200 mm<br>— width of more than 10 mm but not more than 200 mm<br>— length of more than 10 mm but not more than 200 mm<br>equipped with at least two fixing holes, made of aluminium alloys ENAC-46100 or ENAC-42100 (based on the norm EN:1706) with following characteristics:<br>— internal porosity not more than 1 mm;<br>— outer porosity not more than 2 mm;<br>— Rockwell hardness HRB 10 or more<br>of a kind used in the production of suspensions systems for engines in motor vehicles | 0 %                           | 31.12.2019                                  |
| *ex 8108 90 30                                  | 50             | Titanium-aluminium-vanadium alloy (TiAl6V4) wire, complying with AMS standards 4928, 4965 and 4967                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 0 %                           | 31.12.2015                                  |
| ex 8108 90 50                                   | 80             | Plates, sheets, strips and foil of non-alloyed titanium<br>— of a width of more than 750 mm<br>— of a thickness of not more than 3 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 0 %                           | 31.12.2019                                  |
| ex 8108 90 50                                   | 85             | Strip or foil of non-alloyed titanium:<br>— containing more than 0,07 % by weight of oxygen (O <sub>2</sub> ),<br>— of a thickness of 0,4 mm or more but not more than 2,5 mm<br>— conforming to the Vickers hardness HV1 standard of not more than 170<br>of a kind used in the manufacture of welded tubes for nuclear power plant condensers                                                                                                                                                                                                                                                  | 0 %                           | 31.12.2019                                  |
| *ex 8409 99 00<br>ex 8411 99 00                 | 30<br>70       | Spiral-shaped gas turbine turbocharger component:<br>— with a heat-resistance of not more than 1 050 °C,<br>— with a turbine wheel hole diameter of 30 mm or more, but not more than 110 mm,<br>— whether or not with an engine exhaust manifold                                                                                                                                                                                                                                                                                                                                                 | 0 %                           | 31.12.2018                                  |
| *ex 8411 99 00                                  | 60             | Wheel-shaped gas turbine component with blades, of a kind used in turbochargers:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 0 %                           | 31.12.2017                                  |

| CN code                        | TARI<br>C | Description                                                                                                                                                                                                                                                                                                                                                                                                                | Rate of<br>autonomous<br>duty | Date<br>foreseen for<br>mandatory<br>review |
|--------------------------------|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------|
|                                |           | <ul style="list-style-type: none"> <li>— of a precision-cast nickel based alloy complying with standard DIN G-NiCr13Al6MoNb or DIN G- NiCr13Al16MoNb or DIN NiCo10W10Cr9AlTi or AMS AISI:686,</li> <li>— with a heat-resistance of not more than 1 100 °C;</li> <li>— with a diameter of 30 mm or more, but not more than 100 mm;</li> <li>— with a height of 20 mm or more, but not more than 70 mm</li> </ul>            |                               |                                             |
| ex 8479 89 97                  | 70        | Machine to accurately align and attach lenses into a camera assembly in five axis alignment capability and fix them in position with a two part cure epoxy                                                                                                                                                                                                                                                                 | 0 %                           | 31.12.2019                                  |
| ex 8479 89 97                  | 80        | Machinery for the production of a sub assembled component (anode conductor and the negative closing cap) for the manufacture of AA and/or AAA alkaline batteries (1)                                                                                                                                                                                                                                                       | 0 %                           | 31.12.2019                                  |
| *ex 8483 30 38                 | 40        | Cylindrical bearing housing: <ul style="list-style-type: none"> <li>— of precision-cast grey cast iron complying with standard DIN EN 1561,</li> <li>— with oil chambers,</li> <li>— without bearings,</li> <li>— with a diameter of 50 mm or more, but not more than 250 mm,</li> <li>— with a height of 40 mm or more, but not more than 150 mm,</li> <li>— whether or not with water chambers and connectors</li> </ul> | 0 %                           | 31.12.2017                                  |
| ex 8501 32 00<br>ex 8501 33 00 | 60<br>15  | Traction motor, with: <ul style="list-style-type: none"> <li>— a torque output of 200 Nm or more but not more than 300 Nm</li> <li>— a power output of 50 kW or more but not more than 100 kW</li> <li>— a speed of not more than 12 500 rpm</li> </ul> for use in the manufacture of electric vehicles (1)                                                                                                                | 0 %                           | 31.12.2019                                  |
| ex 8504 40 88                  | 30        | DC to AC inverter for use in traction motor control for use in the manufacture of electric vehicles (1)                                                                                                                                                                                                                                                                                                                    | 0 %                           | 31.12.2019                                  |
| ex 8504 40 90                  | 80        | Power converter containing: <ul style="list-style-type: none"> <li>— a DC to DC converter</li> <li>— a charger of a capacity of not not more than 7 kw</li> <li>— switching functions</li> </ul> for use in the manufacture of electric vehicles (1)                                                                                                                                                                       | 0 %                           | 31.12.2019                                  |
| ex 8505 90 20                  | 30        | Coil for an electromagnetic valve, with: <ul style="list-style-type: none"> <li>— a plunger</li> <li>— a diameter of 12,9 mm (+/- 0,1),</li> <li>— a height without plunger of 20,5 mm (+/- 0,1),</li> <li>— an electric cable with connector, and</li> </ul> in a cylindrical metal housing                                                                                                                               | 0 %                           | 31.12.2019                                  |
| *ex 8507 10 20                 | 30        | Lead-acid accumulators or -modules, of a kind used for starting piston engines with <ul style="list-style-type: none"> <li>— a nominal capacity of not more 32 Ah,</li> <li>— a length of not more than 205 mm,</li> <li>— a width of not more than 130 mm and</li> <li>— a height of not more than 190 mm</li> </ul> for use in the manufacture of articles of CN-code 8711 (1)                                           | 0 %                           | 31.12.2018                                  |
| *ex 8507 60 00                 | 85        | Rectangular modules for incorporation in lithium-ion rechargeable batteries: <ul style="list-style-type: none"> <li>— of a length of 312 mm or more, but not more than 350 mm</li> <li>— of a width of 79,8 mm or more, but not more than 225 mm</li> <li>— of a height of 35 mm or more, but not more than 168 mm</li> <li>— of a weight of 3,95 kg or more, but not more than 8,56 Kg</li> </ul>                         | 0 %                           | 31.12.2015                                  |

| CN code        | TARI<br>C | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Rate of<br>autonomous<br>duty | Date<br>foreseen for<br>mandatory<br>review |
|----------------|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------|
| *ex 8507 60 00 | 87        | — with a rating of 66,6 Ah or more, but not more than 129 Ah<br>Lithium-ion rechargeable batteries, with:<br>— a length of 1 475 mm or more, but not more than 2 820 mm<br>— a width of 935 mm or more, but not more than 1 660 mm<br>— a height of 260 mm or more, but not more than 600 mm<br>— a weight of 320 kg or more, but not more than 700 kg<br>— a nominal capacity of 18,4 Ah or more, but not more than 130 Ah,<br>— put up in packs of 12 or 16 modules | 0 %                           | 31.12.2017                                  |
| *ex 8511 30 00 | 30        | Igniter integrated coil assembly with:<br>— an igniter,<br>— a coil on plug assembly with an integrated mounting bracket,<br>— a housing,<br>— a length of 90 mm or more but not more than 200 mm (+/- 5 mm),<br>— an operating temperature of -40 °C or more but not more than 130 °C,<br>— a voltage of 10,5 V or more, but not more than 16 V                                                                                                                      | 0 %                           | 31.12.2019                                  |
| ex 8512 20 00  | 10        | Fog lamps with galvanised inner surface, containing:<br>— plastic holder with four or more brackets,<br>— one or more, but not more than two 12 V bulbs,<br>— connection cable with a connector,<br>— plastic cover<br>for use in the manufacture of goods of chapter 87<br>(1)                                                                                                                                                                                       | 0 %                           | 31.12.2019                                  |
| ex 8512 20 00  | 20        | Information screen displaying at least time, date and status of safety features in a vehicle with an operating voltage of 12 V or more, but not more than 14,4 V, of a kind used in the manufacturing of goods of Chapter 87                                                                                                                                                                                                                                          | 0 %                           | 31.12.2019                                  |
| ex 8512 30 90  | 10        | Horn assembly operating on piezomechanical principle for generating a specific sound signal, with a voltage of 12 V, comprising:<br>— coil,<br>— magnet,<br>— metal membrane,<br>— connector,<br>— holder<br>of a kind used in the manufacture of goods of Chapter 87                                                                                                                                                                                                 | 0 %                           | 31.12.2019                                  |
| ex 8512 90 90  | 10        | Ultrasonic parking sensor with<br>— printed circuit board inside the housing and sensor cell on the cover connected through terminal pins,<br>— an operating voltage of not more than 12 V,<br>— ability to receive and transmit signals processed by the control unit<br>of a kind used in the manufacturing of goods of Chapter 87                                                                                                                                  | 0 %                           | 31.12.2019                                  |
| ex 8514 20 80  | 10        | Cavity assembly comprising at least:                                                                                                                                                                                                                                                                                                                                                                                                                                  | 0 %                           | 31.12.2019                                  |
| ex 8516 50 00  | 10        | — a transformer with an input of not more than 240 V and an output of not more than 3 000 W                                                                                                                                                                                                                                                                                                                                                                           |                               |                                             |
| ex 8516 60 80  | 10        | — an AC or DC fan motor with an output of not more than 42 watts<br>— a housing made of stainless steel<br>— with or without a magnetron of a microwave output power of not more than 900 W<br>for use in the manufacture of built-in products of CN-codes 8514 2080, 8516 5000 and 8516 6080<br>(1)                                                                                                                                                                  |                               |                                             |
| ex 8516 90 00  | 80        | Door assembly incorporating a capacitive sealing element and wavelength choke for use in the manufacture of built-in products of CN-codes 8514 2080, 8516 5000 and                                                                                                                                                                                                                                                                                                    | 0 %                           | 31.12.2019                                  |

| CN code                         | TARI<br>C | Description                                                                                                                                                                                                                                                                                                                                                                                                             | Rate of<br>autonomous<br>duty | Date<br>foreseen for<br>mandatory<br>review |
|---------------------------------|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------|
|                                 |           | 8516 6080<br>(1)                                                                                                                                                                                                                                                                                                                                                                                                        |                               |                                             |
| ex 8518 90 00                   | 80        | Integrated car loudspeaker housing, consisting of:<br>— a speaker frame and magnet system holder with a protective coating and<br>— an embossed anti-dust cloth                                                                                                                                                                                                                                                         | 0 %                           | 31.12.2019                                  |
| *ex 8525 80 19                  | 60        | Image scanning cameras, using:<br>— a „Dynamic“- or „Static overlay lines“ system,<br>— an output NTSC video signal,<br>— a voltage of 6,5 V or more,<br>— an illuminance of 0,5 lux or more                                                                                                                                                                                                                            | 0 %                           | 31.12.2019                                  |
| *ex 8527 91 99<br>ex 8529 90 65 | 20<br>85  | Assembly consisting of at least:<br>— an audio frequency amplifier unit, comprising at least an audio frequency amplifier and a sound generator,<br>— a transformer and<br>— a radio broadcast receiver<br>for use in the manufacture of consumer electronic products<br>(1)                                                                                                                                            | 0 %                           | 31.12.2019                                  |
| ex 8529 10 80                   | 70        | Ceramic filters<br>— with an applicable frequency range of 10 kHz or more but no more than 100 MHz<br>— with a housing of ceramic plates provided with electrodes<br>of a kind used in electrical-mechanical transducer or resonator in audio visual and communication equipment                                                                                                                                        | 0 %                           | 31.12.2019                                  |
| ex 8529 90 65                   | 80        | Tuner transforming high-frequency signals into digital signal, for use in the manufacture of products falling under heading 8527<br>(1)                                                                                                                                                                                                                                                                                 | 0 %                           | 31.12.2019                                  |
| *ex 8529 90 92<br>ex 8548 90 90 | 15<br>60  | LCD modules,<br>— solely consisting of one or more TFT glass or plastic cells,<br>— not combined with touch screen facilities,<br>— with one or more printed circuits boards with control electronics for pixel addressing only,<br>— with or without backlight unit and<br>— with or without inverters                                                                                                                 | 0 %                           | 31.12.2018                                  |
| ex 8537 10 99                   | 40        | Electronic control unit for monitoring car vehicle tyre pressure comprising plastic box with printed circuit board inside and with or without metal holder, of:<br>— a length of 50 mm or more, but not more than 120 mm,<br>— a width of 20 mm or more but not more than 40 mm,<br>— a height of 30 mm or more, but not more than 120 mm<br>of a kind used in the manufacture of goods of Chapter 87                   | 0 %                           | 31.12.2019                                  |
| ex 8537 10 99                   | 50        | Electronic control unit BCM (Body Control Module) comprising<br>— plastic box with printed circuit board and metal holder,<br>— with voltage of 9V or more, but not more than 16V,<br>— able to control, evaluate and manage functions of assisting services in an automobile, at least wiper timing, window heating, interior lighting, seat belt reminder<br>of a kind used in the manufacture of goods of Chapter 87 | 0 %                           | 31.12.2019                                  |
| ex 8537 10 99                   | 60        | Electronic assembly consisting of:<br>— a microprocessor,<br>— light-emitting diode (LED) or liquid crystal display (LCD) indicators,                                                                                                                                                                                                                                                                                   | 0 %                           | 31.12.2019                                  |

| CN code                        | TARI C   | Description                                                                                                                                                                                                                                                                                                                                                    | Rate of autonomous duty | Date foreseen for mandatory review |
|--------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------------------|
|                                |          | — electronic components mounted on a printed circuit, for use in the manufacture of built-in products of CN-codes 8514 2080, 8516 5000 and 8516 6080<br>(1)                                                                                                                                                                                                    |                         |                                    |
| ex 8544 49 91                  | 10       | Insulated copper electrical wires:<br>— with individual conductor wires of a diameter exceeding 0,51 mm.,<br>— for a voltage of not more than 1 000 V,<br>for use in the manufacture of automotive cable harnesses<br>(1)                                                                                                                                      | 0 %                     | 31.12.2019                         |
| *ex 8548 90 90                 | 65       | LCD modules,<br>— solely consisting of one or more TFT glass or plastic cells,<br>— combined with touch screen facilities,<br>— <i>with</i> one or more printed circuits boards with control electronics for pixel addressing only,<br>— with or without backlight unit and<br>— with or without inverters                                                     | 0 %                     | 31.12.2018                         |
| ex 8708 30 10                  | 10       | Brake unit assembly comprising<br>— electric control brake,<br>— stroke sensor,<br>— VDC (vehicle dynamic control) and<br>— backup power source<br>for use in the manufacture of vehicles<br>(1)                                                                                                                                                               | 0 %                     | 31.12.2019                         |
| ex 8708 30 91                  | 20       | Non-asbestos organic brake pads with friction material mounted to the band steel back plate for use in the manufacture of goods of Chapter 87<br>(1)                                                                                                                                                                                                           | 0 %                     | 31.12.2019                         |
| ex 8708 30 91                  | 30       | Body of disc type brake in BIR ("Ball in Ramp") or EPB ("Electronic Parking Brake") version containing functional and mounting openings and guide grooves, of a kind used in the manufacture of goods of Chapter 87                                                                                                                                            | 0 %                     | 31.12.2019                         |
| ex 8708 91 35                  | 10       | Aluminium cooler using compressed air with a ribbed design of a kind used in the manufacture of goods of Chapter 87                                                                                                                                                                                                                                            | 0 %                     | 31.12.2019                         |
| ex 8708 94 35                  | 20       | Rack steering gear in aluminium housing with homokinetic hinges of a kind used in the manufacture of goods of Chapter 87                                                                                                                                                                                                                                       | 0 %                     | 31.12.2019                         |
| ex 9002 11 00                  | 80       | Lens assembly with:<br>— a field of view range of 58,5 deg or more, but not more than 194 deg,<br>— a focal length of 1,16 mm or more, but not more than 3,88 mm,<br>— a relative aperture of F/2.0 or more but not more than 2.6,<br>— a diameter of 17 mm or more but not more than 18,5 mm,<br>for use in the manufacture of CMOS automotive cameras<br>(1) | 0 %                     | 31.12.2019                         |
| ex 9029 10 00                  | 30       | Speed sensor using the Hall effect for measuring wheels rotation in a motor vehicle equipped with plastic housing and attached to connecting cable with a joining connector and mounting holders of a kind used in the manufacture of goods of Chapter 87                                                                                                      | 0 %                     | 31.12.2019                         |
| ex 9029 20 31<br>ex 9029 90 00 | 10<br>20 | Clustered instrument panel with the microprocessor control board, stepping motors and LED indicators showing at least:<br>— speed,<br>— engine revolutions,<br>— engine temperature,<br>— the fuel level<br>communicating via CAN-BUS and K-LINE protocols, of a kind used in the                                                                              | 0 %                     | 31.12.2019                         |

| CN code       | TARI<br>C | Description                                                                                                                                                                                                                                                                                                                                          | Rate of<br>autonomous<br>duty | Date<br>foreseen for<br>mandatory<br>review |
|---------------|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------------------------------------------|
| ex 9031 80 34 | 50        | manufacture of goods of Chapter 87<br><br>Programmable dual linear Hall sensor<br>— consisting of two non-electrically connected integrated circuits, a top die and a bottom die,<br>— positioned on the top and bottom of a lead frame,<br>— in a semiconductor housing,<br>for use as a means for measuring angles, positions and currents in cars | 0 %                           | 31.12.2019                                  |
| ex 9031 80 38 | 50        | Gyroscopic sensor for measuring lateral acceleration of the vehicle vertical axis comprising<br>— a piezoelectric crystal for generating an electrical potential during deformation and<br>— a plastic box with metal holder<br>of a kind used in the manufacture of goods of Chapter 87                                                             | 0 %                           | 31.12.2019                                  |
| ex 9031 80 38 | 60        | Congestion sensor, printed circuit board and connector, moulded together in plastic, for monitoring congestion "G" and providing the values for further evaluation of triggering the airbags, of a kind used in the manufacture of goods of Chapter 87                                                                                               | 0 %                           | 31.12.2019                                  |
| ex 9031 80 98 | 30        | Functional Test Machine for calibrating and image quality testing lenses in automotive cameras                                                                                                                                                                                                                                                       | 0 %                           | 31.12.2019                                  |

(1) Suspension of duties is subject to Articles 291 to 300 of Commission Regulation (EEC) No 2454/93 of 2 July 1993 laying down provisions for the implementation of Council Regulation (EEC) No 2913/92 establishing the Community Customs Code (OJ L 253, 11.10.1993, p. 1).

(2) However, the measure is not allowed where processing is carried out by retail or catering undertakings.

(c) the following rows for the products with the CN and TARIC codes are deleted:

| CN code       | TARIC |
|---------------|-------|
| ex 2009 89 73 | 11    |
| ex 2009 89 73 | 13    |
| ex 2009 89 99 | 93    |
| ex 2207 20 00 | 20    |
| ex 2207 20 00 | 80    |
| ex 2818 10 91 | 10    |
| ex 2915 90 70 | 40    |
| ex 2921 45 00 | 10    |
| ex 2927 00 00 | 15    |
| ex 2932 99 00 | 35    |
| ex 2934 99 90 | 33    |
| ex 3204 20 00 | 40    |
| ex 3811 21 00 | 43    |
| ex 3811 21 00 | 53    |
| ex 3820 00 00 | 20    |
| ex 3824 90 92 | 52    |
| ex 3901 10 10 | 10    |
| ex 3901 10 10 | 20    |
| ex 3901 90 90 | 30    |
| ex 3901 90 90 | 40    |
| ex 3901 90 90 | 50    |
| ex 3903 19 00 | 30    |
| ex 3912 20 11 | 10    |
| ex 3919 10 80 | 21    |
| ex 3919 10 80 | 65    |
| ex 3919 90 00 | 21    |
| ex 3919 90 00 | 37    |

| CN code       | TARIC |
|---------------|-------|
| ex 3919 90 00 | 57    |
| ex 3920 61 00 | 20    |
| ex 3920 62 19 | 81    |
| ex 7606 12 92 | 20    |
| ex 7607 11 90 | 10    |
| ex 7607 11 90 | 20    |
| ex 8108 90 30 | 30    |
| ex 8411 99 00 | 30    |
| ex 8411 99 00 | 40    |
| ex 8483 30 38 | 30    |
| ex 8504 50 95 | 60    |
| ex 8507 10 20 | 85    |
| ex 8507 60 00 | 35    |
| ex 8507 60 00 | 70    |
| ex 8511 30 00 | 20    |
| ex 8525 80 19 | 35    |
| ex 8527 21 59 | 10    |
| ex 8527 29 00 | 20    |
| ex 8527 29 00 | 30    |
| ex 8527 91 99 | 10    |
| ex 8529 90 65 | 35    |
| ex 8529 90 92 | 44    |
| ex 8543 70 90 | 13    |
| ex 8543 70 90 | 23    |
| ex 8548 90 90 | 47    |
| ex 8548 90 90 | 49    |
| ex 8548 90 90 | 55    |
| ex 9405 40 39 | 50    |
| ex 9405 40 39 | 60    |



| CN code       | TARIC |
|---------------|-------|
| ex 9405 40 99 | 03    |
| ex 9405 40 99 | 06    |

(2) Annex II is amended as follows:

(a) the following rows for the supplementary units with the CN and TARIC codes are added:

| CN        | TARIC | SUPPLEMENTARY UNIT |
|-----------|-------|--------------------|
| 9031 8034 | 50    | 1 000 p/st         |
| 8544 4991 | 10    | m                  |
| 3901 1010 | 30    | m <sup>3</sup>     |
| 3901 9090 | 60    | m <sup>3</sup>     |
| 3920 9928 | 65    | m <sup>2</sup>     |
| 3920 9928 | 75    | m <sup>2</sup>     |
| 3921 9060 | 30    | m <sup>2</sup>     |
| 3903 9090 | 45    | m <sup>3</sup>     |
| 3920 7910 | 10    | p/st               |
| 6804 2100 | 10    | p/st               |
| 7616 9910 | 30    | p/st               |
| 8409 9900 | 30    | p/st               |
| 8411 9900 | 60    | p/st               |
| 8411 9900 | 70    | p/st               |
| 8479 8997 | 70    | p/st               |
| 8479 8997 | 80    | p/st               |
| 8483 3038 | 40    | p/st               |
| 8504 4088 | 30    | p/st               |
| 8504 4090 | 80    | p/st               |
| 8505 9020 | 30    | p/st               |
| 8511 3000 | 30    | p/st               |
| 8512 2000 | 10    | p/st               |
| 8512 2000 | 20    | p/st               |
| 8512 3090 | 10    | p/st               |
| 8512 9090 | 10    | p/st               |
| 8514 2080 | 10    | p/st               |
| 8516 9000 | 80    | p/st               |
| 8518 9000 | 80    | p/st               |
| 8529 1080 | 70    | p/st               |
| 8529 9065 | 80    | p/st               |
| 8529 9092 | 15    | p/st               |
| 8537 1099 | 40    | p/st               |
| 8537 1099 | 50    | p/st               |
| 8537 1099 | 60    | p/st               |
| 8548 9090 | 60    | p/st               |
| 8548 9090 | 65    | p/st               |

| CN        | TARIC | SUPPLEMENTARY UNIT |
|-----------|-------|--------------------|
| 8708 3010 | 10    | p/st               |
| 8708 3091 | 20    | p/st               |
| 8708 3091 | 30    | p/st               |
| 8708 9135 | 10    | p/st               |
| 8708 9435 | 20    | p/st               |
| 9029 1000 | 30    | p/st               |
| 9029 2031 | 10    | p/st               |
| 9029 9000 | 20    | p/st               |
| 9031 8038 | 50    | p/st               |
| 9031 8038 | 60    | p/st               |
| 9031 8098 | 30    | p/st               |

- (b) the following rows for the supplementary units with the CN and TARIC codes are deleted:

| CN        | TARIC | SUPPLEMENTARY UNIT |
|-----------|-------|--------------------|
| 3901 1010 | 10    | m <sup>3</sup>     |
| 3901 9090 | 30    | m <sup>3</sup>     |
| 8411 9900 | 30    | p/st               |
| 8411 9900 | 40    | p/st               |
| 8483 3038 | 30    | p/st               |
| 8504 5095 | 60    | p/st               |
| 8511 3000 | 20    | p/st               |
| 8527 2900 | 30    | p/st               |
| 8529 9092 | 44    | p/st               |
| 8543 7090 | 13    | p/st               |
| 8543 7090 | 23    | p/st               |
| 8548 9090 | 47    | p/st               |
| 8548 9090 | 49    | p/st               |
| 8548 9090 | 55    | p/st               |
| 9405 4039 | 50    | p/st               |
| 9405 4099 | 03    | p/st               |
| 9405 4099 | 06    | p/st               |